

Ancillary product list

2026

PRODUCT	DESCRIPTION	UNIT OF PURCHASE	CODE
	A lead and rubber universal weathering slate (450 x 450mm code 4 lead base) can be dressed to any tile shape and the unit will accept pipes from 25mm to 125mm in diameter.	Boxes of 5 in: Flat (0 - 20°) Pitched (20 - 40°)	ASL1001 ASL1002
	Fixing clips are a fast and efficient way to fit chase joints of 6mm - 18mm.	Boxes of: 20 x 20 bags 50 x 10 bags	AFX1002 AFX1003
	16mm - 26mm joints	Per Pack: 25 clips in a pack	AFX1010
	Patination oil prevents the unsightly white staining of tiles and brickwork that can occur when lead work is left untreated.	Boxes of: x4 x 500ml x10 x 500ml x4 x 1ltr x10 x 1ltr x12 x 125ml	APT1001 APT1002 APT1003 APT1005 APT1009
	Our high-quality lead-coloured silicone resin sealant ensures a watertight, flexible joint between lead and brickwork or masonry.	Boxes of: 12 tubes of 310ml	ASE1001
	PDV treated softwood timber rolls are used to form lead work joints.	2.4m x 45mm Pack of 10	AFX1001

Ancillary product list

2026

PRODUCT	DESCRIPTION	UNIT OF PURCHASE	CODE
	Midland Lead supply two different types of membranes: Lead underlay: A non-woven polyester felt underlay isolates the lead from the roof deck allowing it to respond more easily to thermal movement, also allowing air movement below the lead, so that any trapped moisture dries out. Building paper: Best used as cladding underlay in uninsulated buildings, separation layer or lead roofing underlay in heritage projects.	Both lead underlay and building paper are supplied in rolls of 25m x 1m	AML1001 AML1002
	Lead Dome Sets Lead domes are used to fix lead sheet for decorative purposes.	Pack of 20	AFX1007
	All Lead Slate Lead slates are used to provide a weather-tight joint for flues and soil stacks that penetrate the roof. Slates are made of base of code 4 lead (450mm x 450mm) and are either designed for flat or pitched roofs.	Individual units, with pipe diameters: Pitched 110mm (4")* Flat 110mm (4")* *Other sizes are available upon request	ASL1003 ASL1004
	Flexible Lead Joints A flexible lead joint - made of code 5 lead and rubber - is designed to overcome the need to fit oversized lead sheet in gutters of all shapes, falls and sizes.	3m x 260mm 3m x 400mm	AFX1008 AFX1009
	Soakers Aluminium soakers are used where a slated or double lap plain-tiled pitched roof abuts a wall. Supplied in packs of 25.	12" - 3 x 3" 300mm x 75mm x 75mm 12" - 4 x 3" 300mm x 100mm x 75mm 6" - 3 x 3" 150mm x 75mm x 75mm 6" - 4 x 3" 150mm x 100mm x 75mm	ASK1001 ASK1002 ASK1003 ASK1004

Ancillary product list

2026

PRODUCT	DESCRIPTION	UNIT OF PURCHASE	CODE
	Stainless Steel Strip Coil Copper Strip are ideal to cut into clips to help prevent lead flashings from lifting in high wind.	20m x 50mm coils that can be cut to length	AFX1004 AFX1005
	Lead Funnel A lead funnel is designed to form the outlet on a timber or cast iron gutter.	Diameter sizes of: 51mm (2") 57mm (2¼")	AFU1001 AFU1002
	Lead Motifs Our range of motifs are ideal to fix lead sheet for decorative purposes. All our motifs can be supplied as individual units.	Round Dot - Large* Round Dot - Small* Tudor Rose - 57mm* *Other designs are available upon request	ADC1001 ADC1002 ADC1003
	Lead Cleaning Gel Our lead cleaning gel is used to remove dirt, grime and stains from old and new lead work. It's also an ideal preparation before putting on patination oil on old lead to restore it.	Boxes of 12 x 125ml bottles	ACG1001

Videos



Fixing Clips

Secure lead into masonry joints with flashing & fixing clips

[Play video →](#)



Patination Oil

Lead treatment with patination oil - protection from white carbonate deposits

[Play video →](#)



Lead Sealant

Lead sealant from Midland Lead

[Play video →](#)



Flexible Lead Slate

How to fix a flexible lead slate

[Play video →](#)