

# ANCILLARY PRODUCT LIST 2019



## COPPER NAILS

Copper nails are ideal to fix lead work. These annular ring shank copper nails have the following measurements: **25mm (length) x 3.55mm (diameter).**


Boxes of **1kg**



## FIXING CLIPS

Fixing clips are a fast and efficient way to fix lead sheet into a joint.


Boxes of:  
**20 bags of 20 clips**  
**10 bags of 50 clips**



## FLEXIBLE LEAD JOINTS

A flexible lead joint - made of **code 5** lead and rubber - is designed to overcome the need to fit oversized lead sheet in gutters of all shapes, falls and sizes.

**260mm x 3m joint**  
**400mm x 3m joint**



## FLEXIBLE LEAD SLATE

A lead and rubber universal weathering slate (**450 x 450mm code 4 lead base**) can be dressed to any tile shape and the unit will accept pipes from **25mm to 150mm in diameter.**

Boxes of 5 in:  
**Flat (0 - 20°)**  
**Pitched (20 - 40°)**




## LEAD CLEANING GEL

Our lead cleaning gel is used to remove dirt, grime and stains from old and new lead work. It's also an ideal preparation before putting on patination oil on old lead to restore it.

Boxes of:  
**12 x 125ml bottles**

# ANCILLARY PRODUCT LIST 2019



## LEAD DOME SETS

Lead domes are used to fix lead sheet for decorative purposes.


Bag of **20 sets**



## LEAD FUNNEL

A lead funnel is designed to form the outlet on a timber or cast iron gutter.


Diameter sizes of:  
**51mm (2")**  
**57mm (2¼")**



## LEAD MOTIFS

Our range of motifs are ideal to fix lead sheet for decorative purposes. All our motifs can be supplied as individual units.


**Round dot: Small/Large**  
**Tudor rose**



## LEAD SEALANT

Our high-quality lead-coloured silicone resin sealant ensures a watertight, flexible joint between lead and brickwork or masonry.

Box containing  
**12 tubes of 310ml**



## LEAD SLATE

Lead slates are used to provide a weather-tight joint for flues and soil stacks that penetrate the roof. Slates are made of base of **code 4 lead (450mm x 450mm)** and are either designed for flat or pitched roofs.

Individual units, with pipe diameters:  
**75mm (3")\***  
**100mm (4")**  
**125mm (5")\***  
**150mm (6")\***

\*lead time of up to 7 working days

# ANCILLARY PRODUCT LIST 2019



## MEMBRANES

### PRODUCT

### DESCRIPTION

### AVAILABLE IN:

Midland Lead supply two different types of membranes:

**Lead underlay:** A non-woven polyester felt underlay isolates the lead from the roof deck allowing it to respond more easily to thermal movement, also allowing air movement below the lead, so that any trapped moisture dries out.

**Building paper:** Best used as cladding underlay in uninsulated buildings, separation layer or lead roofing underlay in heritage projects.

Both lead underlay and building paper are supplied in rolls of **25m x 1m**



## PATINATION OIL

Patination oil prevents the unsightly white staining of tiles and brickwork that can occur when lead work is left untreated.

Boxes of:

**12 x 125ml bottles**  
**4 x 0.5l bottles**  
**10 x 0.5l bottles**  
**4 x 1l bottles**  
**10 x 1l bottles**



## SOAKERS

Aluminium soakers are used where a slated or double lap plain-tiled pitched roof abuts a wall.

Supplied in packs of 25

**150mm x 75mm x 75mm**  
(6" x 3" x 3")  
**150mm x 100mm x 75mm**  
(6" x 4" x 3")  
**300mm x 75mm x 75mm**  
(12" x 3" x 3")  
**300mm x 100mm x 75mm**  
(12" x 4" x 3")



## STRIP

Our strip comes in two materials:

**Copper strip** is ideal to cut into clips to help prevent lead flashings from lifting in high wind.

**Stainless steel strip** is ideal to cut into clips to help prevent lead flashings from lifting in high wind.

Both strips are supplied in:

**20m x 50mm coils**  
that can be cut to length



## WOODCORE ROLL

PDV treated softwood timber rolls are used to form lead work joints. Rolls are supplied in **bundles of 10.**

**2.4m lengths**