# **ANCILLARY PRODUCT LIST 2015**



#### **Copper nails**

Copper nails are ideal to fix lead work. These annular ring shank copper nails have the following measurements: 25mm (length) x 3.55mm (diameter).

**Supplied in:** Copper nails are available in boxes of 1kg



#### Flexible lead joints (multi-joint)

A flexible lead joint - made of code 5 lead and rubber - is designed to overcome the need to fit oversized lead sheet in gutters of all shapes, falls and sizes.

Available in: 260mm x 3m joint 400mm x 3m joint



## Flexible lead slate (multi-slate)

A lead and rubber universal weathering slate (450 x450mm code 4 lead base) can be dressed to any tile shape and the unit will accept pipes from 25mm to 150mm in diameter.

Available in boxes of 5 in: Flat (0 - 20°) Pitched (20 - 40°)



## **Fixing clips**

Fixing clips are a fast and efficient way to fix lead sheet into a joint.

Available in boxes of: 20 bags of 20 clips 10 bags of 50 clips



#### Lead cleaning gel

Our lead cleaning gel is used to remove dirt, grime and stains from old and new lead work. It's also an ideal preparation before putting on patination oil on old lead to restore it.

Available in boxes of: 1 x 1 litre bottle 12 x 125ml bottles





# Lead dome sets

Lead domes are used to fix lead sheet for decorative purposes.

Supplied in a bag of 20 sets.



# Lead funnel

A lead funnel is designed to form the outlet on a timber or cast iron gutter.

Supplied in diameter sizes of: 51mm (2") 57mm (2¼") 63mm (2½")



#### **Membranes**

Midland Lead supply two different types of membranes:

- Lead underlay: A non-woven polyester felt underlay isolates the lead from the roof deck allowing it to respond more easily to thermal movement, also allowing air movement below the lead, so that any trapped moisture dries out.
- Building paper: Best used as cladding underlay in uninsulated buildings, separation layer or lead roofing underlay in heritage projects.

Both lead underlay and building paper are supplied in rolls of 25m x 1m Lead underlay Building paper



## Lead tools

Our range of lead tools are specifically designed for working with lead – making your job easier and giving the lead the perfect finish. All our tools can be supplied as individual units.

Our range includes: Bending stick Bossing mallet: Small Medium Bossing stick Chase wedge Lead dresser: Small Medium Large Lead knife Setting in stick









Our strip comes in two materials:

- Copper strip is ideal to cut into clips to help prevent lead flashings from lifting in high wind.
- Stainless steel strip is ideal to cut into clips to help prevent lead flashings from lifting in high wind.

Supplied in:

Both strips are supplied in 20m x 50mm coils that can be cut to length. Cooper strip Stainless steel strip



#### **Soakers**

Aluminium soakers are used where a slated or double lap plain-tiled pitched roof abuts a wall.

Aluminium soakers are used where a slated or double lap plain-tiled pitched roof abuts a wall

150mm x 75mm x 75mm (6" x 3" x 3") 150mm x 100mm x 75mm (6" x 4" x 3") 175mm x 100mm x 75mm (7" x 4" x 3") 300mm x 75mm x 75mm (12" x 3" x 3") 300mm x 100mm x 75mm (12" x 4" x 3") 330mm x 100mm x 75mm (13" x 4" x 3")



#### Lead sealant

Our high-quality lead-coloured silicone resin sealant ensures a watertight, flexible joint between lead and brickwork or masonry.

**Supplied in box containing** 12 tubes of 310ml.



#### Lead slate

Lead slates are used to provide a weather-tight joint for flues and soil stacks that penetrate the roof. Slates are made of base of code 4 lead (450mm x 450mm) and are either designed for flat or pitched roofs.

Supplied as individual units, with pipe diameters as follows:

75mm (3") 100mm (4") 125mm (5") 150mm (6")





# Lead motifs

Our range of motifs are ideal to fix lead sheet for decorative purposes. All our motifs can be supplied as individual units.

Our range includes: Acom English rose Fleur de leys Round dot: Small Large Rope Sea horse Tudor rose Yorkshire rose



## **Patination oil**

Patination oil prevents the unsightly white staining of tiles and brickwork that can occur when lead work is left untreated.

Supplied in boxes of:  $12 \times 125$ ml bottles  $24 \times 125$ ml bottles  $4 \times 0.5$ l bottles  $10 \times 0.5$ l bottles  $4 \times 1$ l bottles  $10 \times 1$ l bottles



#### Woodcore roll

PDV treated softwood timber rolls are used to form lead work joints. Rolls are supplied in bundles of 10 and come in 2 sizes.

Available in 2 dimensions: 1.2m lengths 2.4m lengths

