LEAD FLASHING

WEIGHT CHART



		CODE 3		CODE 4		CODE 5		CODE 6		CODE 7		CODE 8			
WIDTH mm Norn Imp		GREEN 3 metre 6 metre Kg Kg		BLUE 3 metre 6 metre Kg Kg		RED 3 metre 6 metre Kg Kg		BLACK 3 metre 6 metre Kg Kg		WHITE 3 metre 6 metre Kg Kg		ORANGE 3 metre 6 metre Kg Kg		WIDTH mm Nom Imp	
150	6"	7.0	13.5	9.0	18.5	11.5	23.0	13.5	27.0	16.0	32.0	18.0	36.0	150	6"
180	7"	8.0	16.0	11.0	22.0	14.0	27.5	16.5	32.5	19.5	38.5	22.0	43.5	180	7 "
210	8"	9.5	19.0	13.0	26.0	16.0	32.0	19.0	38.0	22.5	45.0	25.5	51.0	210	8"
240	9"	11.0	21.5	15.0	29.5	18.5	36.5	22.0	43.5	26.0	51.5	29.0	58.0	240	9"
270	10"	12.0	24.5	16.5	33.0	20.5	41.0	24.5	49.0	29.0	58.0	32.5	65.0	270	10"
300	12"	13.5	27.0	18.5	36.5	23.0	45.5	27.0	54.0	32.0	64.5	36.0	72.5	300	12"
330	13"	15.0	30.0	20.0	40.5	25.0	50.5	30.0	59.5	35.5	71.0	40.0	80.0	330	13"
360	14"	16.0	32.5	22.0	44.0	27.5	55.0	32.5	65.0	38.5	77.0	43.5	87.0	360	14"
390	15"	17.5	35.0	24.0	48.0	30.0	59.5	35.0	70.5	42.0	83.5	47.0	94.0	390	15"
420	16"	19.0	38.0	26.0	51.5	32.0	64.0	38.0	76.0	45.0	90.0	51.0	101.5	420	16"
450	18"	20.5	40.5	27.5	55.0	34.5	68.5	40.5	81.5	48.0	96.5	54.5	109.0	450	18"
480	19"	21.5	43.0	29.5	59.0	36.5	73.0	43.5	87.0	51.5	103.0	58.0	116.0	480	19"
510	20"	23.0	46.0	31.0	62.5	39.0	78.0	46.0	92.0	55.0	109.5	61.5	123.0	510	20"
540	21"	24.5	48.5	33.0	66.0	41.0	82.5	49.0	97.5	58.0	116.0	65.0	130.5	540	21"
570	22"	26.0	51.5	35.0	70.0	43.5	87.0	51.5	103.0	61.0	122.0	69.0	138.0	570	22"
600	24"	27.0	54.0	37.0	73.5	46.0	91.5	54.0	108.5	64.5	128.5	72.5	145.0	600	24"
750	30"	34.0	67.5	46.0	92.0	57.0	114.5	68.0	135.5	80.5	161.0	90.5	181.0	750	30"
900	36"	40.5	81.0	55.0	110.0	68.5	137.0	81.5	162.5	96.5	193.0	109.0	217.5	900	36"
1000	39"	45.0	90.0	61.0	122.5	76.0	152.5	90.5	×.	107.0	553	121.0	250	1000	39"
1050	41"	47.5	94.5	64.5	128.5	80.0	160.0	95.0	-	112.5	920	127.0	-	1050	41"
1200	47"	54.0	108.0	73.5	147.0	91.5	183.0	108.5	-	128.5	383	145.0	-	1200	47"
1350	53"	61.0	121.5	83.0	165.5	103.0	206.0	122.0	-	145.0	0.00	163.0	3.00	1350	53"
1400	55"	63.0	126.0	86.0	171.5	107.0	213.5	126.5	-	150.0	150	169.0	-	1400	55"
WEIGHT per sq.m		15.0kg		20.4kg		25.4kg		30.1kg		35.7kg		40.3kg		WEIGHT per sq.m	
THICKNESS		1.32mm (0.052")		1.80mm (0.071")		2.24mm (0.088")		2.65mm (0.104")		3.15mm (0.124")		3.55mm (0.140")		THICKNESS	

Flashings: Standard flashings are shown in the above chart, however, any widths from 100mm (4") to 1400mm (4"7") can be produced.

Lead flashings theory weights:

All theory weights are subject to ±5% tolerance.

The theory weight of lead sheet in kgs can be calculated using the following formula: No. of pieces x Length in metres x Width in metres x Thickness in mm x 11.34

Useful conversion factors:

1mm = 0.039 Inches 1m = 3.281 Feet 1m = 39,370 Inches 1 Inch = 25.4mm 1 Foot = 304.8 mm1 Yard = 914.4 mm

DON'T FORGET TO APPLY PATINATION OIL



C€

Midland Lead Ltd Kiln way, Woodville, Swadlincote, Derbyshire DE11 8ED United Kingdom

T: +44 (0)1283 224555 F: +44 (0)1283 550284 E: sales@midlandlead.co.uk www.midlandlead.co.uk













